

MaraX

PL62X



TECHNICAL FEATURES

L58E group with mechanical pre-infusion compatible with LELIT58 barista tools

Double probe HX System with thermosyphon circulation (Patent pending)

Silent pump

Temperature configuration button (Warm - Hot - Extra Hot)

Mode setting button (Xmode coffee or Xmode steam)

Steam boost

Stand-by function

Professional water-steam taps with spring closure

Machine ready and/or warming-up LED

Lack of water in the tank or no-tank LED

Active "Reserve mode"

I/O stainless steel back-lit switch

Double manometer for pump/steam pressure

Brushed stainless steel appliance body with cup warmer rack and drip tray with wire grate

Anti-burn multidirectional steam and hot water wands

Mug friendly

Coffee machine with L58E group and automatic control of the extraction temperature. The perfect coffee at the right temperature in just 24 minutes, stable thermal equilibrium with any coffee blend.

Boiler: 1.8 l with AISI316L stainless steel heat-exchanger

Water tank: 2.5 l

Dimensions LxDxH: 22.5x52x35.5 cm

Weight: 18.5 kg

DELIVERED WITH

LELIT58 2-ways filterholder with classic polished black handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 2 doses filter (18-21 g), IMS

LELIT58 blind filter, IMS

LELIT58 stainless steel tamper with red wooden handle

Spoon for coffee powder

Cup rack

35 l water softener filter

First cleaning kit

Small brush with nylon bristles

PL62X 230 V 50 Hz | Plug Type E+F

PL62X-AUS-4120 220-240 V 50/60 Hz | Plug Type I

PL62X-AS 220 V 60 Hz | Plug Type G

PL62X-120 120 V 60 Hz | Plug Type B

PL62X-2G82 220-240 V 50/60 Hz | Plug Type G

MaraX

PL62X-EUCB



TECHNICAL FEATURES

L58E group with mechanical pre-infusion compatible with LELIT58 barista tools

Double probe HX System with thermosiphon circulation (Patent pending)

Silent pump

Temperature configuration button (Warm - Hot - Extra Hot)

Mode setting button (Xmode coffee or Xmode steam)

Steam boost

Stand-by function

Professional water-steam taps with spring closure

Machine ready and/or warming-up LED

Lack of water in the tank or no-tank LED

Active "Reserve mode"

I/O stainless steel back-lit switch

Double manometer for pump/steam pressure

Black appliance body with textured finish

Cup warmer rack and drip tray with wire grate

Maple wood knobs and lever

Anti-burn multidirectional steam and hot water wands

Mug friendly

Black coffee machine with L58E group and dual probe HX system. The perfect coffee at the right temperature in just 24 minutes, stable thermal equilibrium with any coffee blend.

Boiler: 1.8 l with AISI316L stainless steel heat-exchanger

Water tank: 2.5 l

Dimensions LxDxH: 22.5x52x35.5 cm

Weight: 18.5 kg

DELIVERED WITH

LELIT58 2-ways filterholder with maple wooden handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 2 doses filter (18-21 g), IMS

LELIT58 blind filter, IMS

LELIT58 stainless steel tamper with maple wooden handle

Spoon for coffee powder

Cup rack

35 l water softener filter

First cleaning kit

Small brush with nylon bristles

PL62X-EUCB 230 V 50 Hz | Plug Type E+F

PL62X-120CB 120 V 60 Hz | Plug Type B

PL62X-AUS-4120 220-240 V 50/60 Hz | Plug Type I

PL62X-2G82 220-240 V 50/60 Hz | Plug Type G

MaraX

PL62X-EUCW



TECHNICAL FEATURES

L58E group with mechanical pre-infusion compatible with LELIT58 barista tools

Double probe HX System with thermosiphon circulation (Patent pending)

Silent pump

Temperature configuration button (Warm - Hot - Extra Hot)

Mode setting button (Xmode coffee or Xmode steam)

Steam boost

Stand-by function

Professional water-steam taps with spring closure

Machine ready and/or warming-up LED

Lack of water in the tank or no-tank LED

Active "Reserve mode"

I/O stainless steel back-lit switch

Double manometer for pump/steam pressure

White appliance body with textured finish

Cup warmer rack and drip tray with wire grate

Maple wood knobs and lever

Anti-burn multidirectional steam and hot water wand

Mug friendly

White coffee machine with L58E group and dual probe HX system. The perfect coffee at the right temperature in just 24 minutes, stable thermal equilibrium with any coffee blend.

Boiler: 1.8 l with AISI316L stainless steel heat-exchanger

Water tank: 2.5 l

Dimensions LxDxH: 22.5x52x35.5 cm

Weight: 18.5 kg

DELIVERED WITH

LELIT58 2-ways filterholder with maple wooden handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 2 doses filter (18-21 g), IMS

LELIT58 blind filter, IMS

LELIT58 stainless steel tamper with maple wooden handle

Spoon for coffee powder

Cup rack

35 l water softener filter

First cleaning kit

Small brush with nylon bristles

PL62X-EUCW 230 V 50 Hz | Plug Type E+F

PL62X-120CW 120 V 60 Hz | Plug Type B

PL62X-AUS-4140 220-240 V 50/60 Hz | Plug Type I

PL62X-2G40 220-240 V 50/60 Hz | Plug Type G